



Heike Christopher (Autor)

A compact mode-locked diode laser system for high precision frequency comparison experiments




64

Forschungsberichte aus dem

Ferdinand-Braun-Institut,
Leibniz-Institut
für Höchstfrequenztechnik

Innovationen mit Mikrowellen & Licht

A compact mode-locked diode laser system for high precision frequency comparison experiments



Heike Christopher

<https://cuvillier.de/de/shop/publications/8418>

Copyright:

Cuvillier Verlag, Inhaberin Annette Jentsch-Cuvillier, Nonnenstieg 8, 37075 Göttingen, Germany

Telefon: +49 (0)551 54724-0, E-Mail: info@cuvillier.de, Website: <https://cuvillier.de>

Contents

| | |
|---|-----------|
| 1. Introduction | 1 |
| 1.1. The optical frequency comb | 2 |
| 1.1.1. Theoretical description of mode-locked operation | 4 |
| 1.1.2. Phenomenological description of mode-locked operation | 5 |
| 1.1.3. Measurement of optical frequencies and frequency differences | 6 |
| 1.2. A tailored optical frequency comb for a spaceborne experiment | 7 |
| 1.2.1. The QUANTUS experiments: a test of the universality of free fall | 8 |
| 1.2.2. An advanced frequency stabilization scheme for future QUANTUS experiments | 9 |
| 1.2.3. The LASUS projects: development of diode laser technology for use in the QUANTUS experiments | 13 |
| 1.2.4. Requirements on an optical frequency comb for spaceborne tests of the universality of free fall in the QUANTUS experiments | 16 |
| 1.3. State of the art optical frequency combs operating in the wavelength region around 780 nm | 20 |
| 1.4. Thesis organization | 23 |
| 1.4.1. Goals of this thesis | 23 |
| 1.4.2. Outline of this thesis | 23 |
| 2. Mode-locking of semiconductor lasers | 25 |
| 2.1. Introduction to mode-locked diode lasers | 25 |
| 2.2. Diode laser chips | 25 |
| 2.3. Mode-locking techniques | 29 |
| 2.3.1. Active mode-locking | 29 |
| 2.3.2. Passive mode-locking | 30 |
| 2.3.3. Hybrid mode-locking | 32 |
| 2.4. Optical absorption and gain in passively mode-locked diode lasers | 33 |
| 2.5. Resonator concepts for passively mode-locked diode lasers | 36 |
| 2.6. Optical components of an ML-ECDL | 38 |
| 2.6.1. Coating of the diode laser chip's facets | 39 |
| 2.6.2. Beam shaping optics | 39 |
| 2.6.3. External mirror | 40 |
| 3. Measurement methods and setup | 41 |
| 3.1. Introduction to measurement and analysis feedback loop | 41 |
| 3.2. Requirements on the experimental setup and techniques | 41 |

| | |
|---|------------|
| 3.3. Experimental setup | 43 |
| 3.3.1. Laser test mount | 43 |
| 3.3.2. Measurement setup | 45 |
| 3.4. Experimental techniques | 47 |
| 3.4.1. Optical frequency domain | 47 |
| 3.4.2. RF frequency domain | 48 |
| 3.4.3. Time domain-based investigation of RF characteristics | 51 |
| 3.4.4. Time domain | 54 |
| 3.4.5. Optical power | 56 |
| 3.4.6. Measurement procedure and control | 57 |
| 3.5. Performance analysis | 59 |
| 3.6. Summary | 60 |
| 4. Development of a diode laser-based optical frequency comb | 61 |
| 4.1. Introduction to the evaluation | 61 |
| 4.2. Influence of the laser design parameters on the mode-locking performance | 62 |
| 4.2.1. Optical design | 62 |
| 4.2.2. External mirror | 63 |
| 4.2.3. Laser resonator length | 64 |
| 4.2.4. Epitaxial layer design of the diode laser chip | 67 |
| 4.2.5. Longitudinal design of the diode laser chip | 75 |
| 4.2.6. Facet reflectivity of the diode laser chip | 82 |
| 4.2.7. Conclusion for optimization of the laser design | 87 |
| 4.3. Influence of the laser operating parameters on the performance of the best suited device | 88 |
| 4.3.1. Optical frequency domain characteristics | 88 |
| 4.3.2. RF frequency domain characteristics | 93 |
| 4.3.3. Time domain-based RF characteristics | 94 |
| 4.3.4. Time domain characteristics | 96 |
| 4.3.5. Optical power characteristics | 97 |
| 4.4. Conclusion of the development of the diode laser-based optical frequency comb | 98 |
| 5. Micro-integration of the diode laser-based optical frequency comb generator | 101 |
| 5.1. Introduction to the micro-integration concept | 101 |
| 5.2. First generation ML-ECDL module | 101 |
| 5.2.1. The micro-integration technology platform | 101 |
| 5.2.2. Integration strategy | 103 |
| 5.2.3. Mode-locking performance | 106 |
| 5.2.4. Conclusions from the first generation micro-integrated ML-ECDL | 109 |
| 5.3. Advanced ML-ECDL module | 110 |
| 5.3.1. The micro-integration technology platform | 110 |
| 5.3.2. Integration strategy | 112 |
| 5.3.3. Mode-locking performance | 116 |
| 5.3.4. Conclusion from the advanced ML-ECDL module | 125 |

| | |
|--|------------|
| 5.4. Conclusion from micro-integration of a diode laser-based optical frequency comb generator | 126 |
| 6. Pulse repetition rate stabilization | 127 |
| 6.1. Introduction to stabilization of the pulse repetition rate | 127 |
| 6.2. Experimental setup | 127 |
| 6.3. Results | 131 |
| 6.3.1. RF characteristics | 131 |
| 6.3.2. Optical characteristics | 133 |
| 6.3.3. Temporal and optical power characteristics | 134 |
| 6.4. Conclusion from the stabilization of the pulse repetition rate | 134 |
| 7. Conclusion and outlook | 137 |
| 7.1. Conclusion | 137 |
| 7.2. Outlook on future advancements | 139 |
| A. Derivation of equations | 143 |
| A.1. Influence of the spectroscopy stabilization in the advanced stabilization scheme | 143 |
| A.2. Optical gain and absorption | 143 |
| Lists of figures | 145 |
| Lists of tables | 149 |
| List of abbreviations | 151 |
| List of symbols | 155 |
| Bibliography | 161 |
| List of publications | 179 |
| Acknowledgments | 183 |
| Selbständigkeitserklärung | 185 |